

Safety Data Sheet

Section 1, Identification

Product identifier

Product Name: GraficBraid Graphite Braided Packing

Chemical Name: Graphite/Flexible Graphite

Trade Name: GraficBraid, Style 1000, 1000W

Manufacturer/Supplier's Name: Mineral Seal Corporation

Address (Number, Street, City, State and ZIP Code): 1832 S. Research Loop, Tucson, AZ 85710

Emergency Telephone Number: (520) 885-8228

Telephone Number for Information: (520) 885 - 8228

Recommended use: Gasket and fluid sealing material,

Restrictions: Not established

Section 2, Hazard(s) identification

Hazard classification(Physical, Health, OSHA): Not classified

Label elements: No

Hazard Symbol: None

Signal Word: None

Hazard statement: None

Precautionary statement (Prevention, Response, Storage, Disposal): None

Hazard statements: None

Hazards not otherwise classified: None

Section 3, Composition/information on ingredients

Including chemical ingredients and trade secret claims

Ingredient	CAS Number	%(By Weight)
Graphite	7782-42-5	90%
(Mineral Graphite, Carbon)		
Crystalline Silica	14808-60-7	< 0.2%
(Impurity ash, silica, silica dioxide, quartz)		
Fiberglass filament	65997-17-3	< 5 %
Proprietary Binder Material	ND	< 3 %
Optional Reinforcement Wire, enhancement additives	ND	Varies

Section 4, First-aid measures

First-aid measures:

RESPIRATORY TRACT IRRITATION:

Move the person to a dust free location. Get medical attention if the irritation continues.

EYE IRRITATION:

Flush with large amounts of water. Get medical attention if irritation persists.

SKIN IRRITATION:

Wash area of contact thoroughly with soap and water. Get medical attention if irritation persists.

GASTROINTESTINAL IRRITATION:

Unlikely to happen. However, if gastrointestinal tract irritation develops, move the person to a dust free environment.

Most Important symptoms and effects, both acute and delayed: None

Indication of any immediate medical attention and special treatment required: None

Other possible effects:

The product is not hazardous material in normal use. High concentration of graphite dust may be irritating to eyes, skin and respiratory tract. Inhalation of high concentration of graphite dust over prolonged periods of time may cause pneumoconiosis.

Section 5, Fire-fighting measures

Suitable extinguishing media: Flexible graphite is not flammable. Use extinguishing media suitable for type of surrounding fire. The product should be cooled with water

Specific hazards arising from the substance: Thermal decomposition may produce smoke and oxides of carbon.

Special protective equipmenmt and actions for firfighters: None

Section 6, Accidental release measures

Personal precautions, protective equipment and emergency procedures: None

Environmental precautions: Do not release the material to sewers or drains.

Methods and material for containment and cleaning up: Spill should be returned to the original container, or if not reusable, should be placed in container for disposal.

Section 7, Handling and storage

Precautions for safe handling and storage: Normal handling and storing of graphite does not require special precautions. Minimize accumulation of graphite debris and dusts in work area. Graphite is electrical conductive. Graphite debris and dusts may cause shorting of electrical circuits or equipment malfunctioning.

Conditions for safe storage including any incompatibilities: Store in original container in a dry area. Keep container closed when not in use. No known incompatible substances under normal conditions.

Section 8, Exposure controls/personal protection

OSHA's Permissible Exposure Limits (PELs); Threshold Limit Values (TLVs); appropriate engineering controls; personal protective equipment (PPE).

Occupational exposure limits

Ingredient	C.A.S. No.	Agency	Type Limit	Additional
				Comments
Flexible Graphite	7782-42-5	OSHA Z-1	PEL 5mg/m3 (Respirable)	
(carbon,			PEL 15mg/m3 (Total dust)	
mineral graphite)		OSHA Z-3	TWA 15 million particles	
		ACGIH	TLV TWA 2mg/m3 (Respirable)	
		NIOSH	TWA 2.5 mg/m3 (Respirable)	
Crystalline Silica	14808-60-7	OSHA Z-3	TWA 0.3mg/m3 (Total dust)	
(impurity ash,			TWA 0.1mg/m3 (Respirable)	
silica, quartz silica			TWA 2.4 million particles	
dioxide)		ACGIH	TLV TWA 0.025mg/m3 (Respirable)	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

Appropriate engineering controls: Local exhaust ventilation, dust collection, and other equipment designed to minimize dust.

Personal protective equipment (PPE) and protection measures:

Eye/face protection: If dusts or debris are generated during processing, wear safety glasses with side shields or other forms of eye protection in compliance with appropriate OSHA standards.

Skin hand protection: Wear gloves to prevent cuts, abrasions and irritation during handling and processing. Respiratory protection: When exposure is above limit, half-facepiece, or full-facepiece air purifying respirator equipped with a NIOSH certified P95 particulate filter cartridge or PAPR with tight-fitting full facepiece is recommended depending on the exposure level.

Section 9, Physical and chemical properties

ODOR AND APPEARANCE: Black, odorless, solid shape

CHEMICAL FAMILY: Graphite: Carbon

BOILING POINT: N/A

WATER SOLUBILITY (%): Not Soluble in Water

MELTING POINT: 5400° F

SPECIFIC GRAVITY: 0.8- 1.7

VAPOR PRESSURE: N/A

pH: N/A

VAPOR DENSITY (Air = 1): N/A

% VOLATILE: N/A

MOLECULAR FORMULA: C

Section 10, Stability and reactivity

CHEMICAL STABILITY: Stable under conditions of normal use

INCOMPATIBILITY: Strong oxidizing agent.

CONDITIONS TO AVOID: None.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon dioxide CO2

HAZARDOUS POLYMERIZATION: N/A

Section 11, Toxicological information

Signs and Symptoms of Exposure:

Inhalation: No adverse effects under normal exposure conditions

Respiratory Tract Irritation: No adverse effects under normal exposure conditions

Skin Contact: No adverse effects under normal exposure conditions Eye Contact: No adverse effects under normal exposure conditions Ingestion: No adverse effects under normal exposure conditions

Toxicological data:

Acute Toxicity

Name	Route	Species	Value
Graphite	Oral	Rat	LD50 > 10000 mg/kg

Skin corrosion/irritation: No adverse effects are expected.

Serious eye damage/eye irritation: No adverse effects are expected.

Respiratory sensitization: No Data. Skin sensitization: Not a skin sensitizer

Central Nervous System (CNS) Depression: Very unlikely, no data available

Peripheral Neuropathy: Very unlikely, no data available

Reproductive/Developmental Toxicity: No data

Germ cell mutagenicity: No data

Carcinogenicity: Graphite is not classified

Impurity ash crystalline silica is classified as known or suspected human carcinogen by IATC, NTP and

ACGIH

Single exposure may cause target organ effects: No data

Prolonged or repeated exposure may cause target organ effects: No data

Aspiration hazard: Not classified.

Chronic effects: Unlikely

Section 12, Ecological information

Ecotoxicity: Not an environmental hazard Persistence and degradability: Not degradable Bioaccumulative potential: Not applicable

Mobility in soil: No data

Mobility in general: Not applicable

Other adverse effects: No known other adverse effects to the environment

Section 13, Disposal considerations

Disposal instructions: Recover and recycle if practical, or approved landfill. This substance is not specifically listed as hazardous waste in federal regulations. For particular situation check federal, local, regional, state or provincial regulations to identify all applicable disposal requirements.

Hazardous waste code: Not established

Waste from residues / unused products: Follow the same disposal instructions for the product. Contaminated packaging Dispose: Follow the disposal requirements for the packaging material.

Section 14, Transport information

Graphite is not regulated as dangerous goods by the following agencies: DOT, IATA, IMDG.

UN number: Not assigned

UN proper shipping name: Not specified Transport hazard class(es): Not classified Packing group, if applicable: Not applicable

Environmental hazards (e.g., Marine pollutant (Yes/No)): No

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): Not available

Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport

or conveyance either within or outside their premises: None

Section 15, Regulatory information

US Federal Regulations

Under some use conditions, this material may be considered to be hazardous in accordance with OSHA 29 CFR 1910.1200.

US State Regulations

WARNING: This product contains chemicals known to the State of California to cause cancer: Impurity Ash Content: Crystalline silica CAS 14808-60-7 (less than 0.2%) California Proposition 65 Carcinogens & Reproductive Toxicity (CRT): Listed substance

International Regulations

This product is listed by multiple countries as inventory chemical substance in complies with the inventory requirements administered by the governing country.

Section 16, Other information

NFPA Hazard Classification

Health: 0 Flammability: 0 Instability: 0 Special Hazards: None

Date of preparation/last revision: September 19, 2023

Version: 1.00

This Safety Data Sheet was prepared in accordance with OSHA 1910.1200 Hazard Communication Standard (HCS 2012).

DISCLAIMER: The information provided in this Safety Data Sheet (SDS) is believed to be correct as of the date of preparation and to the best of our knowledge. Mineral Seal Corporation (Minseal) makes no warranties. Users should use this information to make an independent determination of the safety of their workers and the environment. Users should provide the information in this form to their employees or contractors that are involved in handling of the substances. Users are responsible for determining whether the product is fit for a particular purpose and application.